

V No	Description	Technical information
20	'T' Fitting	I.D 115mm. Length 300mm. To Fit V25,V26. No need for a V22
21	90' bend	ID 115mm. Length200mm per side. To fit V25,V26. No need for a V22
22	Coupling	ID 115mm. Width 200mm. To connect V25 and V26.
24	End cap	ID 115mm. To suit all 110mm pipe and connectors.
25	Solid carrier pipe	ID 100mm. Standard length 3 meters. OD 114mm to fit inside fittings.
26	Slotted carrier pipe	ID 100mm Standard length 1.2 meters OD 114mm to fit inside fittings.
29	Voidformer outlet connector	To fit V51. Pipe length 990mm (with a slit of 30mm x 930mm).
31	Voidformer voidformer connector	ID 53mm Standard length 915 To fit V32. Special coupling needed.
32	Gas vent pipe 50mm	ID 43mm Length up to 5m. Supplied with custom coupling to fit V31.
34	Voidformer outlet connector	Width 915 mm. Connector length 350mm to connect voidformer and V51 or PAGv53 for use with pipes.
35	Voidformer outlet connector	Width 990mm. Connector length 150 to fit V25
36	Voidformer outlet connector	Width 915mm. Connector length 190mm to fit 25mm voidformer and V25
40	Square vent box	Width 425mm. Height 400mm. Stainless Steel slotted grill as standard. Open area 65,000mm ²
41 HSF	Round gully vent	185mm OD. Security screwed slotted stainless grill. Total maximum height 1030mm
42 HSF	Rectangular vent	420mm x230mm. Security screwed slotted stainless grill. Total maximum height1080mm.
50	Air brick	Standard size 70 x 220mm. Black as standard. Open area 6,500mm ² . To fit V51.
51	Adjustable periscope vent	Adjusts between a rise of 210mm and 360mm. Width 210mm. May be sealed with tape. To fit V53, V29, V34 and V50
53	Round to rectangular converter	ID 115mm. To connect V25 to be connected to V51

Jan 2017